SECTION 27 00 00
COMMUNICATIONS BASIC REQUIREMENTS

PART 1 - GENERAL

1.01 SUMMARY

A. This Section specifies the common administration basic requirements and common methods for all low voltage systems installation work included under Division 27 and 28 and where those requirements differ from the requirements of this section, the more stringent shall govern.

1.02 STANDARDS, REGULATIONS, AND CODES REFERENCES

A. The following Standards, Regulations and Codes apply to work specified in the Contract Documents.
   1. Applicable State and Local Codes.
   2. California Building Code and California E4h6(ann)2.2 1e1dD .00 0 39( )Tj-0.001 Tc 0.003 Tw 1.217 0 28[C)

2. Electrical symbols indicating wiring and equipment shown in the Contract Documents are included in the Contract unless specifically noted otherwise.
3. Examine the entire set of Drawings to avoid conflicts with other systems. Determine exact route and installation of communications wiring and equipment with conditions of construction.

3.02 INSTALLATION

A. Install communications equipment completely as directed by manufacturer's installation instructions. Obtain installation instructions from manufacturer prior to rough-in of the communications equipment, examine the instructions thoroughly. When requirements of the installation instructions conflict with the Contract Documents, request clarification from Project Manager/Designer prior to proceeding with the installation.

B. Do not install communications equipment in obvious passages, doorways, scuttles, or crawl spaces which would impede or block the passage's intended usage.

C. Do not install communications equipment in locations where it would obviously be subject to damage during normal usage.

3.03 FIELD QUALITY CONTROL

A. Tests: Conduct tests of equipment and systems to demonstrate compliance with requirements specified in Division 27 & 28. Refer to individual Specification Sections for required tests. Document tests and include in Closeout Documents.

3.04 CLEANING

A. Remove dirt and debris caused by the execution of the communications work.

B. Leave the entire communications system installed under this Contract in a clean, dust-free, and proper working order.

C. Vacuum clean interiors of new and modified electrical signal and communication equipment enclosures.

END OF SECTION

A. See Division 26 for requirements.

B. Approved manufactures are Jensen, Christy or approved equal.

C. All ground boxes shall have metal traffic-rated lids with permanent factory markings of COMM or COMMUNICATIONS.

D. Minimum size is 17” x 30”

2.08 PENETRATION SEALING

A. Firestopping: Provide UL Listed Firestopping materials for all penetrations through rated assemblies (walls / floors).

B. Draft stopping: Foam sealant for use around conduit penetrations (in non-rat (9 (i)7.65.9 (r.3 (t)-3 (o)-6.6t(o)-

B. Hanger spacing shall be 48” or less and within 12” of sleeves and/or junction/back boxes.

3.04 LOW VOLTAGE PATHWAY/RACEWAYS

A. EMT conduit may be used at following locations (see Division 26 for exact requirements):
   1. In dry locations in furred spaces.
   2. In partitions other than concrete or solid masonry.
   3. In protected exterior locations not exposed to direct weather.

B. Rigid steel conduit and fittings shall be used for vertical risers and on top of all roofs, overhangs, walkways, canopies, or any other location exposed to direct weather. See Division 26 for exact requirements.

C. Furnish and install pull lines in all unused (empty) conduits or raceways. All pull lines shall be permanently tagged with identification at both ends.

D. Install exposed conduit neatly, parallel to or at right angles to structural members. Maintain a minimum of 12 inches of clearance from steam or hot water pipes. All installed strut channel supports should allow for future conduit attachments. The width of strut channel to match the width of the closest attached junction box. See design document details for attachment requirements.

E. Supports: Support conduit with two-hole straps or strut channel where shown in design documents

I. Clean, prep and paint with white primer all exposed conduit, junction boxes, channel strut, fittings, and accessories.

J. Before pulling any conductors into an underground PVC conduit (new or existing), the conduit shall be first be proofed by pulling through a mandrel of a diameter ¼ in. smaller than the conduit inside dia., followed by a swab of the same diameter as the conduit inside diameter.

K. Non-metallic raceway to be installed with mechanical fasteners only, do not remove adhesive tape backing.

K. CAPPING

1. Cap conduits during construction with manufactured seals. Swab out conduits before installing wires.

2. Cap all empty conduits below grade and in pull boxes with manufacturer's caps to prevent entrance of debris, attach pull string to cap.

3.05 J-BOXES

A. Screws shall be used to attach boxes, and must be accurately placed for finish, independently and securely supported by adequate wood backing or by manufactured adjustable channel type heavy-duty box hangers.

1. Boxes shall be attached to metal studs with metal box hangers.

2. Boxes installed in masonry tile or concrete block construction shall be secured with auxiliary plates, bars or clips and be grouted in place.

B. Locate outlets at the following heights unless otherwise noted on Drawings, Specifications, current CBC or as required to meet ADA handicap requirements.

1. Data Outlets: Same height as electrical outlets

2. Telephone Wall Outlets: Above counter/backsplash height or at electrical switch height.

C. Boxes shall be placed within 18” of electrical outlets.

D. For sound control, separate outlets on opposite sides of walls 16" minimum. Where outlets are less than 16" or in sound rated walls, seal airtight with fire rated sheet putty pads. Fill gap between junction box and wall with acoustical sealant all around perimeter of junction box. Fill conduits larger than 1 1/4" with fire rated putty.

E. Installation of conduit and outlet boxes in fire-resistive walls, floors, floor-ceiling or roof-ceiling assemblies shall comply with Title 24, Part 2, Section 713.

3.06 UNDERGROUND BOXES

A. To be installed per Division 26 requirements.

B. Provisions to be made for supporting cables from the box sides (i.e., j-hooks, d-rings)

3.07 SLEEVES AND CONDUIT PENETRATIONS

A.

3.09 FINAL DOCUMENT SUBMITTALS

A. See 27 00 00 for more information.

END OF SECTION

1.03 RELATED REQUIREMENTS

A. The General Conditions, Supplementary Conditions and Division 1 are fully applicable to this Section, as if repeated herein.

B. Section 27 00 00 – Communications

C. Section 27 05 00 – Common Work Results for Communication Systems.

1.04 INDUSTRY GUIDELINES AND STANDARDS

A. California Electrical Code (CEC) – Current adopted version

B. California Building Code (CBC) – Current adopted version.

C. ANSI/TIA-568.0-D – Generic Communications Cabling for Customer Premises.

D. ANSI/TIA-568.1-D – Commercial Building Communications Cabling Standard Part 1: General Requirements.

E. ANSI/TIA 568-C.2 – Balanced Twisted-Pair Telecommunications Cabling and Components Standards

F. ANSI/TIA 568.3-D – Optical Fiber Cabling Components Standard

G. ANSI/TIA-569-D – Commercial Building Standard for Telecommunications Pathways and Spaces.

J. ANSI/TIA-606-B – Administration Standard for the Commercial Telecommunications Infrastructure.

K. ANSI/JSTD-607-C – Commercial Building Bonding and Grounding (Earthing) Requirements for Telecommunications.

1.05 QUALIFICATIONS

A. The contractor shall possess a California C7 or C10 license.

B. The Contractor or Subcontractor shall have 5 years' documented experience.

1.06 SYSTEM REQUIREMENTS

A. Any new installations or existing system modifications shall seamlessly integrate into the site's existing data cable plan system.

1.07 CONTRACTOR "SHOP DRAWINGS" DESIGN REQUIR RE

3. Bond metallic equipment (including ladder rack) to the grounding bus bar, using not smaller than No. 6 AWG equipment grounding conductor.

3.06 WORKMANSHIP

A. Quality workmanship is a high priority for the District and the Contractor shall be held to a high-level of professional workmanship.

B. The District' Project or Construction Manager will have the authority to reject Work which does not conform to the Drawings and Specifications.
B

C. Comply with highest industry standards, except when specified requirements indicate more rigid standards or more precise workmanship.

D. Perform Work with persons experienced and qualified to produce workmanship specified.

REVISION SUMMARY

SECTION 27 51 23.50
EDUCATIONAL INTERCOM SYSTEMS

PART I - GENERAL

accessories,
necessary for the proper installation of a turn-key Assistive Listening system to the District.

2. The contractor will coordinate with the District in writing for any needed information (i.e. IP addresses, etc.) 10 business days prior to the date the information is needed.

B. The District has standardized on Rauland Telecenter U equipment and the installing Contractor shall be Rauland Telecenter authorized.

C. For existing construction – provide and install all components and accessories to modify the existing system while maintaining code compliance and to seamlessly integrate the new components into the existing campus' system. Prior to beginning any work, the Contractor is responsible for identifying any existing system errors or faults and bring these issues to the attention of the District Project Manager.

D. The Contractor shall be responsible for programming the Rauland Telecenter Intercom System.

E.

H. The Contractor shall adjust any speaker levels to the appropriate level as determined in system testing.

I. Existing systems shall remain operable until the new system is accepted and approved by the District or the District's representative.

J. The Contractor is responsible for user/operator training (maximum 2 hours).

K. The Contractor shall complete all required project closeout documentation in a timely fashion.

1.03 RELATED REQUIREMENTS

A. The General Conditions, Supplementary Conditions and Division 1 are fully applicable to this Section, as if repeated herein.

B. Section 27 00 00 - Communications

C. Section 27 05 00 – Common Work Results for Communication Systems.

E. Section 27 10 00 – Structured Cabling

1.04 REFERENCES

A. See section 27 00 00 for requirements.

1.05 DE[C)4e0 se-e8 tEiRo2n2 0E0R0B for requirements.

1.05 E59.4ee s9e0 (r)2 7100 90 (9 1123 P261 3 (sm 2.989 (Y)2 1) Tj 85.007

B. Contractor shall be located within 50 miles

D. Perform all Work as indicated in the Drawings and Specifications.

E. All low voltage cables shall be kept away from power circuits.

F. Contractor shall provide programming and configuration of the Educational Intercom system for full functionality.

G. Contractor shall maintain a complete, up-to-date backup of the system configuration. Backup shall be maintained throughout programming period until final Acceptance by District. Submit back-ups to District upon Final Acceptance.

3.06 LABELING/SCHEDULES

A. All labels are to be machine generated black letters on white adhesive label stock that is appropriate for the installation environment (interior/exterior).

B. Label all standard speaker cables with port ID.

C. Label all speakers with speaker ID.

D. Label all IP speakers with MDF/IDF, patch panel and jack numbers.

3.09 CONFIGURATION

A. All equipment to be fully configured and tested for functionality prior to testing.

3.10 FIELD QUALITY CONTROL AND TESTING

A. Upon reaching substantial completion, perform a complete test and inspection of the system. If found to be installed and operating properly, notify District of your readiness to perform the formal Test & Inspection of the complete system.

B. Submit the Record Drawings (as-builts) to District for review prior to inspection.

C. During the formal Test & Inspection (Commissioning) of the system, have personnel available with tools and equipment to inspect wiring, devices, and system operation.

D. If corrections are needed, the Contractor will be provided with a Punch-List of all discrepancies. Perform the needed corrections in a timely fashion.

E. Notify the District when ready to perform a re-inspection of the installation.

F. District or its representative to provide final sing-off for acceptance.

3.11 AS-BUILT DRAWINGS

A. See section 27 00 00 for requirements.

B. As-built riser diagram showing all access control components for site.

3.12 TRAINING

A.

Wire and Cable	**West Penn**	

END OF APPENDIX
END OF SECTION

SECTION 27 53 13
CLOCK SYSTEMS

PART I - GENERAL

1.01 SUMMARY

A. This section spAsystem.

installation of a turn-key Clock system to the District.

linate with the District in writing for any needed information (i.e. IP
ess days prior to date the information is needed.

Includes, but is not limited to:

server access

on includes (io)-N6w.c8(pz1c1t6.wh8(l[Tu9z(aI)]T0.0002.8(ip8D1.6ckwd8a(a)e3.3v0p0.002a3(i)]TJ0 -1.1 (colat3(es)12.6 k wi0[
switch in the nearest MDF/IDF. Clocks shall synchronize to a network time protocol (NTP) server
as determined by the District.

1.04 REFERENCES

A. See section 27 00 00 for requirements.

1.05 DEFINITIONS

A. See section 27 00 00 for requirements.

1.06 SYSTEM REQUIREMENTS

A. See12 0 T.4 (T)-1REIc(o)-Rj7(i)24ee3 (u)5.37(i)237

PART 3 - EXECUTION

3.00

3.11 AS-BUILT DRAWINGS

A. See section 27 00 00 for requirements.

APPENDIX A – Pre-Approved Materials

DESCRIPTION	MFG	PART NUMBER
Digital Messaging Board, Small	**Rauland**	